DRY CABINET GHIBLI PRO 350

GHIBLI PRO/350L dry cabinet allows to create a safe enviroment to store MSD (Moisture Sensitive Devices). There's no need to configurate the product. Particularly suited for storing highly sensitive MSDs, according to J-STD-033 regulations.



www.maxderbanchi.com



Analyzes variations of humidity and temperature inside the cabinet.

Humidity range	1 ÷ 95%RH
Resolution	0.1%RH
Precision	±2%RH
Temperature	-20 ÷ 60°C
range	
Precision	±1°C
Measures	184x67x44mm
Weight	320gr



Easy to use:

The user doesn't need to set anything. After being plugged in, the cabinet will bring itself to 5% RH.

Security system in case of sensor's fault:

Dehumidifying modules work nonstop and aren't controlled by any sensor. This way they can be easily replace and cannot be affected by sensors' malfunctions.

Easy calibration:

The cabinet will be supplied with a portable hygrometre, visible from the upper glass pane. It allows to measure humidity and temperature inside the cabinet and has a datalogger to visualise and analise data from the comodity of your PC.

Technical Specifications:

Code	20839
Humidity range	5% guaranteed (tipically 2%)
External measures	580x767x895mm (feet excluded)
Internal measures	520x755x860mm
Weight	47kg
Shelves	2 height-adjustable (458x606x18mm)
Structure	1,2mm thick steel
Doors	Hermetic closure with key,
	dissipative glass and handle
Power Consumption	Max 250W, average 40W

Easy-to-use

ESD-SAFE paintwork

Incredibly low power usage

Made in Italy

