

via Ludwig Van Beethoven 24 Cinisello Balsamo 20092 (Mi) www.maxderbanchi.com Tel.026600703



THE WORLD LEADER IN **FUME EXTRACTION TECHNOLOGY**

AD Nano

LASER





The compact fume extraction system designed for small scale industrial environments and light in laser coding applications.

The AD Nano fume extraction and filtration system has been designed to provide cost effective solutions for light to medium duty applications. These compact systems are ideal for small scale industrial environments and light laser coding applications. The Reverse Flow Air and DeepPleat DUO filter technology enhances filter performance and ensures longer filter life.

Technology



DeepPleat DUO pre filter



HEPA filter



Reverse flow air (RFA) technology



Advanced carbon filter (ACF) technology



Patented technology



ProTECT service plan



Key features of the AD Nano

Reverse flow air technology

Standard

Long life, low cost replacement filters

Standard

Advanced carbon filter (ACF) and HEPA technology

Standard

Low noise levels

Standard

Remote stop / start interface

Optional

`Easi-Seal` filter location

Standard

DeepPleat DUO pre filter

Standard

Small footprint

Standard

VOC gas sensor (Volatile Organic Compound)

Optional

Filter change / System fail signal

Optional

Contact MAXDER at WWW.MAXDERBANCHI.COM















Technical specification

- 1. Filter condition display
- 2. On / off switch

4. Hose inlet connection - 50mm

- 5. Power cable inlet
- 6. Exhaust outlet
- 7. Motor cooling inlet / outlet

3. Signal / interface cable

8. Castors

- 9. Door hinge
- 10. Door latch







Airflow through filters



Chemical filter



HEPA filter



Pre filter




Clean air



Contaminated air



Particulate



Technical data			
	EU	US	
Dimensions (HxWxD)	770 x 375 x 420mm	30.32 x 14.76 x 16.54"	
Cabinet construction	Brushed stainless steel / Powder coated mild steel	Brushed stainless steel / Powder coated mild steel	
Airflow / Pressure	170m³/hr / 30mbar	100cfm / 30mbar	
Electrical data	230v 50/60Hz Full load current: 1.1 amps / 135 watts	115v 50/60Hz Full load current: 1.2 amps / 135 watts	



MAXDER GROUP S.R.L.

Technical data		
Noise level	< 60dBA (at typical operating speed)	< 60dBA (at typical operating speed)
Weight	40kg	88lbs
Approvals	CE	CE

DeepPleat DUO pre filter specifications		
Surface media area	6m² approx (64.5 ft²)	
Filter media	Glass fibre	
Filter media construction	150mm maxi fold construction with webbing spacers (0.49ft)	
Filter housing	Zintec mild steel	
Filter efficiency	92% @ 0.8 microns	
Inlet size	50mm (0.16ft)	
Dropout chamber size	7.44 litres	

Combined filter specifications	
HEPA filter media	Glass fibre
HEPA media construction	50mm Maxi pleat construction with webbing spacers (0.16ft)
Filter housing	Zintec mild steel
Treated activated carbon	6.75kgs (14.85 lbs)
Filter efficiency	99.997% @ 0.3 microns

Part numbers						
Model	Voltage	Part no.	24V stop / start	Filter change / System failure signal	VOC monitoring	Hose kit
AD Nano powder coated	230V	L2942A	A2001	A2002	A2003	A1020007
AD Nano powder coated	115V	L2941A	A2001	A2002	A2003	A1020007
AD Nano stainless steel	230V	L2952A	A2001	A2002	A2003	A1020007
AD Nano stainless steel	115V	L2951A	A2001	A2002	A2003	A1020007

Replacement filters		
Model	DeepPleat DUO pre filter	Combined filter
AD Nano	A1030190	A1030191

